

Networking / Switches / Unmanaged

# SF-SW0604HIPOE-60

SAFIRE



## Features

---

- Desktop Switch
- 6 mbps ports RJ45 10/100
- 3 PoE+ Ports 30W 802.3af/at + 1 Hi-PoE Port 60W 802.3bt
- Supports PoE power supply up to 60W in total for all ports
- AI Watchdog
- Auto PoE Extended up to 250m 10Mbps

# Specifications

|                               |                                                                                                                                                                                                            |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Interface                     | 4 RJ45 PoE port(s) + 2 Up-link port(s)                                                                                                                                                                     |
| Port speed RJ45               | 4x 10/100Mbps - 2x 10/100Mbps                                                                                                                                                                              |
| PoE features                  | Up to 60W in total for all ports<br>Ports 1~3 PoE+ Up to 30W 802.3af/at<br>Port 4 Hi-PoE Up to 60W 802.3af/at/bt                                                                                           |
| Transmission distance         | Auto PoE Extended 250m a10Mbps<br>There is no need to manually configure the Extended PoE function, the switch automatically detects the distance of the cable and the distance of the cable to the switch |
| Bandwidth                     | 1.2Gbps                                                                                                                                                                                                    |
| MAC Table                     | 2K                                                                                                                                                                                                         |
| Latency                       | 10 to 100MBps <16?s (utilizando 64 byte de tamaño de paquete)                                                                                                                                              |
| AI PoE                        | PoE Watchdog Puertos 1~4 - Reinicio automático de la alimentación de un puerto PoE cuando se detecta un posible fallo.                                                                                     |
| Alimentación                  | Toma Frontal AC 220 V                                                                                                                                                                                      |
| Protecciones                  | 6KV contra Rayos<br>8KV Protección ESD                                                                                                                                                                     |
| Temperatura de funcionamiento | -30° C ~ 60° C                                                                                                                                                                                             |
| Dimensiones                   | 187 (Fo) x 43 (Al) x 139 (An) mm                                                                                                                                                                           |